



PRIMEPAC

making it easy!

PRODUCT SPECIFICATION

Product Name	Grip Film Elite Eco
Product Code	2440
Description	Pre-Stretch Film, 30% Post industrial recycled content



PRODUCT SPECIFICATION

	Spec	Tolerance	Method
Film Width	400mm	Nominal +/- 40mm	
Roll Length	550m	Nominal +/-1%	
Individual Film Weight	1.0kg film only	Nominal +/-10%	
Core Weight	0.158kg	Nominal +/- 2%	
Spot Thickness	5µm	Nominal +/-20%	
Density	0.918g/cm ³	Nominal +/- 10%	
Average Thickness	5µm	Nominal +/- 10%	
Dart Impact Strength	Not less than 50g	Not less than 50g	
Longitudinal Endurance	90kGN/m	Nominal +/-10%	
Traverse Endurance	200kGN/m	Nominal +/-10%	
Recycled Polymer Content	>30%	Nominal +/-2%	
Roll Profile	Oscillated with folded edges		
Core	25mm x 421mm Notched	Nominal +/- 1mm	
Colours & additives	Natural Clear Colour		
Product composition	A base component of LLDPE (Linear low-density polyethylene) & LDPE (low density polyethylene) with a super blend of Polyisobutylene, Butene, Hexene, and Metallocene additives.		
Storage	The product should be stored in a dry place out of direct sunlight at a temperature not greater than 25°C and not less than 5°C to maintain stability.		
Qty on pallet	240 rolls (8rolls/box) 30 boxes per pallet.		
Food usage	The main polymers are in compliance with the food contact legislation, however the PIB is not in compliance with food contact legislation.		

0800 277 772

www.primepac.co.nz

sales@primepac.co.nz

L3 1/61 Constellation Drive, Rosedale, Auckland