

NESS+ SEAL

SPORTY LOOK

NESS+ Seal continues the extension of the popular NESS+ model. NESS+ Seal comes assembled with a gasket & strap for excellent dust protection. Coupled with the exclusive Platinum® fog and scratch resistant coating, NESS+ Seal is designed to enhance your work performance.

✦ PLATINUM®



PSSNESF028 • Clear



PSSNESF417 • Smoke



PSPNESKB04









35g

- ✦ ULTRA WRAP-AROUND FRAME
- ✦ NON-SLIP NOSE BRIDGE
- ✦ ✦ PLATINUM® (✦ P) SCRATCH & FOG RESISTANT COATING
- ✦ PANORAMIC FIELD OF VISION
- ✦ CO-INJECTED PC/TPR TEMPLES FOR GREATER COMFORT
- ✦ "POSITIVE SEAL" GASKET & STRAP KIT TO MAXIMISE PROTECTION IN DUSTY ENVIRONMENTS


bollé
SAFETY

NESS+ SEAL

SPORTY LOOK

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
NESS+ SEAL	 Clear	PSSNESF028	 IO	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/ 
	 Smoke	PSSNESF417	 I3	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/ 
	Gasket + strap kit	PSPNESKB04	-	-	-

LENS MARKING

-  Platinum is a permanent coating applied on both sides of the lens that gives a high resistance to scratching (1.4 cd / m²) and to the most aggressive chemicals and delays the onset of fogging for two minutes, as per the testing requirements of EN166.
- I.** The letter 'I' signifies 'Medium Impact' approval.
- O.** The letter 'O' signifies that the product has been approved for the use both outdoors and indoors, and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

Ocular lens category:

- O.** Range of luminous transmittance 80–100% (Clear).
- 3.** Range of luminous transmittance 8–18% (Smoke)

Others symbols:

-  Manufacturer name

TECHNOLOGIES

PLATINUM

The exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.

LENSES

- 2mm polycarbonate
- Platinum coating on both sides of Clear and Smoke lens
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

FRAME MARKING

AS/NZS 1337.1:2010: Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm ball at 45 m/s.

PACKAGING AND EAN13 CODE			
	PSSNESF028	PSSNESF417	PSPNESKB04
Individual plastic bag	3660740011994	3660740013783	3660740012007
10 safety spectacles per inner box 20 gasket + strap kits	3660740111991	3660740113780	3660740112004
240 safety spectacles per outer pack 480 gasket + strap kits	3660740211998	3660740213787	3660740212001

CHARACTERISTICS	
LENSES	PC – 2mm – Curve 10
FRAME	-
TEMPLES	PC + TPR
STRAP	Nylon/15mm/Adjustable
GASKET/FOAM	Yes
SPARE LENSES	No



21/09/2021

Bollé Safety AU Pty Limited
32–40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: sales@bollesafety.com.au

Hong Kong Bollé Safety
818, 8/F, Ocean Centre, Harbour City,
5 Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
T.: +852 2732 5038

bollesafety.com.au

bolle
SAFETY