

Spot Marking Paint - Fluoro

Safety Data Sheet

SECTION 1: Product identifier

1.1. GHS Product identifier

| | |
|---------------|--|
| Product form | : Mixture |
| Product name | : Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple) |
| Product code | : 7427, 7428, 7429, 7430, 7430, 7431, 7432, 7433 |
| Date Issued | : 9/02/2023 |
| Validity Date | : 9/02/2028 |

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

| | |
|---------------------|--|
| Recommended use | : Use according to manufacturer's directions. Application is by spray atomisation from a hand held aerosol pack. |
| Restrictions on use | : Not to be used for any purpose other than the one the product was designed for |

1.4. Details of manufacturer or importer

PRIMEPAC INDUSTRIAL LTD
45 Noel Burnside Road,
Wiri, Auckland,
New Zealand.
Tel: +64 800 277772
Web: www.primepac.co.nz | email: sales@primepac.co.nz

1.5. Emergency phone number

For more information about poisons or in case of poisoning, call the National Poisons Centre on **0800 764 766**
A free 24/7 service for all New Zealanders

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

| | |
|--|-------------|
| Aerosol, Category 1 | H222 ; H229 |
| Serious eye damage/eye irritation, Category 2A | H319 |

2.2. GHS Label elements, including precautionary statements.

Hazard pictograms (GHS AU):



Flame Exclamation mark

Signal word (GHS AU)

Contains

Hazard statements (GHS AU)

Precautionary statements (GHS AU)

: Danger
 : Ethyl Acetate (< 30 %); Solvent naphtha (petroleum), light aromatic [contains less than 0,1 % w/w benzene] (< 10 %)
 : H222 - Extremely flammable aerosol H229 - Pressurised container: May burst if heated H319 - Causes serious eye irritation
 : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P251 - Do not pierce or burn, even after use.
 P264 - Wash hands, forearms and face thoroughly after handling.
 P280 - Wear eye protection, protective clothing, protective gloves.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
 P501 - Dispose of contents and container to an approved waste disposal plant.
 : AUH044 - Risk of explosion if heated under confinement. Repeated exposure may cause skin dryness or cracking. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENT CAN BE HARMFUL OR FATAL

Additional hazard statements (GHS AU)

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

| Name | CAS-No. | % |
|---------------|-----------|------|
| Ethyl Acetate | 141-78-6 | < 30 |
| Limestone | 1317-65-3 | < 10 |

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
 First-aid measures after skin contact : Wash skin with plenty of water.
 First-aid measures after eye contact : Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If eye irritation persists: Get medical advice/attention.
 First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects after eye contact : Eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Unsuitable extinguishing media are not known.

5.2. Specific hazards arising from the chemical.

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
General measures : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance and protected location. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.

For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

Information on mixed storage : Store away from incompatible materials and products. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity.

Storage area : Keep out of direct sunlight.

Special rules on packaging : Position containers so that any labeling information is visible. Keep packaging closed when not in use. Check containers and packaging regularly for leaks and damage.

Packaging materials : Keep only in original packaging.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Ethyl Acetate (141-78-6)

Australia - Occupational Exposure Limits

| | |
|----------------------|---|
| Local name | Ethyl acetate (Acetic acid ethyl ester; Acetic ester) |
| Regulatory reference | Workplace exposure standards for airborne contaminants (2019) |

Limestone (1317-65-3)

Australia - Occupational Exposure Limits

| | |
|-------------|---|
| OES TWA [1] | 10 mg/m ³ |
| Remark (AU) | This value is for inhalable dust containing no asbestos and < 1% crystalline silica |

8.2. Monitoring methods

Monitoring methods : Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when flammable gases/vapours may be released.

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment. Handle product within a closed system.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment : Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. Avoid all unnecessary exposure. Ocular shower with suitable liquid.

Hand protection : Wear protective gloves

Eye protection : Wear eye protection: Chemical goggles or safety glasses

Skin and body protection : Wear protective clothing: Long sleeved protective clothing

Respiratory protection : If mist is formed : Disposable half mask

Personal protective equipment symbol(s)



Consumer exposure controls : Personal protective equipment (PPE) is not required when handling individual retail pack.

Other information : PPE compliant to the recommended standards should be selected. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

SECTION 9: Physical and chemical properties

Physical state : Liquid

Appearance : Aerosol.

Molecular mass : Not applicable

Colour : Various colours

Odour : Not available

Odour threshold : No data available

pH : Not applicable

pH solution : Not available

Relative evaporation rate (butylacetate=1) : No data available

Melting point / Freezing point : Melting point: Not available

Boiling point : Not available

Flash point : -81 °C (hydrocarbon propellant).

Auto-ignition temperature : Not available

Decomposition temperature : Not available

Flammability : No data available

Vapour pressure : Vapour pressure: Not available

Relative density : Relative vapour density at 20°C: Not available. (Air=1).

Density : Density: ≈ 0.8 kg/l
Relative density: (Water = 1)

Solubility : Water: immiscible

Partition coefficient : Not available

n-octanol/water (Log Pow) : Not available

Viscosity, kinematic : Not available



PRIMEPAC

making it easy!

Explosive properties
Explosive limits
Minimum ignition energy
VOC content
Fat solubility

: Pressurised container: May burst if heated.
: No data available
: No data available
: Not available
: No data available

SECTION 10: Stability and reactivity

Reactivity
Chemical stability
Possibility of hazardous reactions
Conditions to avoid

: Extremely flammable aerosol. Pressurised container: May burst if heated.
: Stable under normal conditions.
: No dangerous reactions known under normal conditions of use.
: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

Incompatible materials
Hazardous decomposition products

: Strong acids. Strong bases. Strong oxidizers.
: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)
Acute toxicity (dermal)
Acute toxicity (inhalation)

: Not classified
: Not classified
: Not classified

Ethyl Acetate (141-78-6)

| | |
|-----------------------------------|--------------------------|
| LD50 oral | 5620 mg/kg bodyweight |
| LD50 dermal | > 18000 mg/kg bodyweight |
| LC50 Inhalation - Rat (Dust/Mist) | 57700 mg/l |

Skin corrosion/irritation
Serious eye damage/irritation
Respiratory or skin sensitization
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
STOT-single exposure

: Not classified
pH: Not applicable
: Causes serious eye irritation.
pH: Not applicable
: Not classified
: Not classified
: Not classified
: Not classified
: May cause drowsiness or dizziness.

Ethyl Acetate (141-78-6)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

STOT-repeated exposure
Aspiration hazard

: Not classified
: Not classified

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

| | |
|----------------------|---------------|
| Vaporizer | Aerosol |
| Viscosity, kinematic | Not available |

Ethyl Acetate (141-78-6)

| | |
|---|-------|
| Animal studies and expert judgment for classification | False |
|---|-------|

Acrylic Resin

| | |
|---|-------|
| Animal studies and expert judgment for classification | False |
|---|-------|



0800 277 772



www.primepac.co.nz



sales@primepac.co.nz



L3 1/61 Constellation Drive, Rosedale, Auckland

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Ethyl Acetate (141-78-6)

| | |
|------------------------------------|--------------------|
| EC50 - Other aquatic organisms [1] | 717 mg/l waterflea |
| EC50 - Other aquatic organisms [2] | 3300 mg/l |

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

| | |
|---|---------------|
| Partition coefficient n-octanol/water (Log Pow) | Not available |
|---|---------------|

12.4 Mobility in soil

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

| | |
|---|---------------|
| Partition coefficient n-octanol/water (Log Pow) | Not available |
|---|---------------|

12.5 Other adverse effects

Ozone : Not classified
 Other adverse effects : No additional information available

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)

| | |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

Ethyl Acetate (141-78-6)

| | |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

Limestone (1317-65-3)




| | |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : When totally empty, containers are recyclable like any other packing.

SECTION 14: Transport information

| ADG | IMDG | IATA |
|--|--|--|
| 14.1. UN number | | |
| 1950 | 1950 | 1950 |
| 14.2. UN Proper Shipping Name | | |
| AEROSOLS | AEROSOLS | Aerosols, flammable |
| 14.3. Transport hazard class(es) | | |
| 2.1 | 2.1 | 2.1 |
|  |  |  |
| 14.4. Packing group | | |
| Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | |
| Dangerous for the environment: No | Dangerous for the environment: No Marine pollutant: No | Dangerous for the environment: No |

14.6 Special precautions for user

Specific storage requirement : No data available

Shock sensitivity : No data available

14.7 Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950

Special provision (ADG) : 63, 190, 277, 327, 344, 381

Limited quantities (ADG) : See SP 277

Excepted quantities (ADG) : E0

Packing instructions (ADG) : P207, LP200

Special packing provisions (ADG) : PP87, L2

Transport by sea

| | |
|-----------------------------------|---|
| UN-No. (IMDG) | : 1950 |
| Special provisions (IMDG) | : 63, 190, 277, 327, 344, 381, 959 |
| Packing instructions (IMDG) | : P207, LP200 |
| Special packing provisions (IMDG) | : PP87, L2 |
| EmS-No. (Fire) | : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES |
| EmS-No. (Spillage) | : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE) |
| Stowage category (IMDG) | : None |
| Stowage and handling (IMDG) | : SW1, SW22 |
| Segregation (IMDG) | : SG69 |

Air transport

| | |
|--|--------------------|
| UN-No. (IATA) | : 1950 |
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provisions (IATA) | : A145, A167, A802 |
| ERG code (IATA) | : 10L |

14.8 Hazchem or Emergency Action Code

| | |
|--------------|------------------|
| Hazchem Code | : Not applicable |
|--------------|------------------|

SECTION 15: Regulatory information

15.1. Safety, health, and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

| | |
|---|----------|
| Australian Inventory of Industrial Chemicals (AICIS Inventory) status | : Listed |
|---|----------|

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

| | |
|----------------------------------|---------------|
| Relevant Poisons Schedule number | : Unscheduled |
|----------------------------------|---------------|

15.2. International agreements

No additional information available



0800 277 772



www.primepac.co.nz



sales@primepac.co.nz



L3 1/61 Constellation Drive, Rosedale, Auckland

SECTION 16: Other information

Indication of changes:

Routine Review - No significant changes from previous issue.

| Indication of changes | | | |
|-----------------------|--|----------|----------|
| Section | Changed Item | Change | Comments |
| | Supersedes | Modified | |
| | Date of revision | Modified | |
| | Issue date | Modified | |
| 1.1 | Product code | Modified | |
| 2.1 | Classification (GHS AU) | Modified | |
| 2.2 | Precautionary statements (GHS AU) | Modified | |
| 2.2 | Additional hazard statements (GHS AU) | Modified | |
| 13.1 | Product/Packaging disposal recommendations | Added | |
| 13.1 | Waste treatment methods | Modified | |
| 16 | Indication of changes | Modified | |

Data sources

: Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals
 Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals
 Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants
 Safe Work Australia - Hazardous Chemical Information System (HCIS)
 Australian Inventory of Industrial Chemicals (AICIS Inventory)
 Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice 2020
 Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017
 Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017
 New Zealand - Chemical Classification and Information Database (CCID)
 New Zealand - Inventory of Chemicals (NZIoC)
 European Chemicals Agency (ECHA) - Annex VI (C&L Inventory)
 European Chemicals Agency (ECHA) - REACH Study Results
 European Chemicals Agency (ECHA) - REACH Registration Dossiers
 United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS)
 Uniform Scheduling of Medicines and Poisons (SUSMP)
 United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation)
 Australian Dangerous Goods Code (ADG Code)
 International Air Transport Association Dangerous Goods Regulations (IATA DGR)
 International Maritime Dangerous Goods (IMDG Code).

Date of revision

: 12/07/2023



0800 277 772



www.primepac.co.nz



sales@primepac.co.nz



L3 1/61 Constellation Drive, Rosedale, Auckland



PRIMEPAC

making it easy!

Classification

| | |
|---------------|-----------|
| Aerosol 1 | H222;H229 |
| Eye Irrit. 2A | H319 |

Full text of H-statements

| | |
|---------------|--|
| Aerosol 1 | Aerosol, Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation, Category 2A |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis |
| H225 | Highly flammable liquid and vapour |
| H319 | Causes serious eye irritation |
| H336 | May cause drowsiness or dizziness |

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.



0800 277 772



www.primepac.co.nz



sales@primepac.co.nz



L3 1/61 Constellation Drive, Rosedale, Auckland