

## Signet Line Marking Paints

### Safety Data Sheet

#### SECTION 1: Product identifier

##### 1.1. GHS Product identifier

Product form	: Mixture
Product name	: Line Marking Paint – Various Colours
Product code	: 8280, 8281, 8282, 8284, 8285, 8286
Date Issued	: 16/10/2023
Validity Date	: 16/10/2028

##### 1.2. Other means of identification

Synonyms	: White, Yellow, Black, Blue, Green, Orange
----------	---

##### 1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Marking Lines. Application is by spray atomisation from a hand held aerosol pack. Use according to manufacturer's directions.
Restrictions on use	: Not to be used for any purpose other than the one the product was designed for

##### 1.4. Details of manufacturer or importer

PRIMEPAC INDUSTRIAL LTD  
45 Noel Burnside Road,  
Wiri, Auckland,  
New Zealand.  
Tel: +64 800 277772  
Web: [www.primepac.co.nz](http://www.primepac.co.nz) | email: [sales@primepac.co.nz](mailto:sales@primepac.co.nz)

##### 1.5. Emergency phone number

For more information about poisons or in case of poisoning, call the National Poisons Centre on **0800 764 766**  
A free 24/7 service for all New Zealanders

#### SECTION 2: Hazard identification

##### 2.1. Classification of the hazardous chemical

###### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317



# PRIMEPAC

*making it easy!*

Specific target organ toxicity – Single exposure,  
Category 3, Narcosis

H336

Specific target organ toxicity – Single exposure,  
Category 3, Respiratory tract irritation

H335

## 2.2. GHS Label elements, including precautionary statements.

Hazard pictograms (GHS AU):



Flame

Exclamation mark

Signal word (GHS AU)

: Danger

Contains

: xylene (10 – 60 %); Ethyl Acetate (< 30 %); Butyl Acetate (< 30 %); High Mol Wt Wetting Agent (< 10 %)

Hazard statements (GHS AU)

: H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS AU)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P251 - Do not pierce or burn, even after use.  
P261 - Avoid breathing spray, mist, gas, fume, vapours.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear eye protection, protective gloves, protective clothing.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Additional hazard statements (GHS AU):

AUH044 - Risk of explosion if heated under confinement.  
AUH066 - Repeated exposure may cause skin dryness or cracking.  
INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENT CAN BE HARMFUL OR FATAL

## 2.3. Other hazards which do not result in classification

No additional information available



0800 277 772



[www.primepac.co.nz](http://www.primepac.co.nz)



[sales@primepac.co.nz](mailto:sales@primepac.co.nz)



L3 1/61 Constellation Drive, Rosedale, Auckland

### SECTION 3: Composition and information on ingredients

Name	CAS-No.	%
xylene	1330-20-7	10 – 60
Ethyl Acetate	141-78-6	< 30
High Mol Wt Wetting Agent	-	< 10

### SECTION 4: First aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

#### 4.3. Medical attention and special treatment

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Unsuitable extinguishing media are not known.

#### 5.2. Specific hazards arising from the chemical.

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
General measures	: No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.



# PRIMEPAC

*making it easy!*

Hazardous decomposition products in case of fire : Toxic fumes may be released.

## 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance and protected location. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.

#### For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.



0800 277 772



[www.primepac.co.nz](http://www.primepac.co.nz)



[sales@primepac.co.nz](mailto:sales@primepac.co.nz)



L3 1/61 Constellation Drive, Rosedale, Auckland

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Does not require any specific or particular technical measures.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Information on mixed storage	: Store away from incompatible materials and products. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity.
Storage area	: Keep out of direct sunlight.
Special rules on packaging	: Position containers so that any labeling information is visible. Keep packaging closed when not in use. Check containers and packaging regularly for leaks and damage.
Packaging materials	: Keep only in original packaging.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

Ethyl Acetate (141-78-6)	
Australia - Occupational Exposure Limits	
Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

### 8.2. Monitoring methods

Monitoring methods	: Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when toxic gases may be released. Gas detectors should be used when flammable gases/vapours may be released.
--------------------	---

### 8.3. Engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Use spark-/explosionproof appliances and lighting system. Use grounded electrical/mechanical equipment. Handle product within a closed system.
----------------------------------	---

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment	: Personal protective equipment (PPE) must be suited to the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. Avoid all unnecessary exposure. Ocular shower with suitable liquid.
Hand protection	: Wear protective gloves
Eye protection	: Wear eye protection: Chemical goggles or safety glasses
Skin and body protection	: Wear protective clothing: Long sleeved protective clothing
Respiratory protection	: Wear appropriate mask: Combined gas/dust mask with filter type



## Personal protective equipment symbol(s)

Other information : PPE compliant to the recommended standards should be selected. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

## SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol with solvent odour.
Molecular mass	: Not applicable
Colour	: Various colours
Odour	: Not available
Odour threshold	: No data available
pH	: Not applicable
pH solution	: Not available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not available
Boiling point	: Not available
Flash point	: -81 °C (hydrocarbon propellant).
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Flammability	: No data available
Vapour pressure	: Vapour pressure: Not available
Relative density	: Relative vapour density at 20°C: Not available. (Air=1).
Density	: Density: 0.85 – 0.95 kg/l
Relative density: (Water = 1).Solubility	: Water: immiscible
Partition coefficient	
n-octanol/water (Log Pow)	: Not available
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s Not available
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: Not available
Fat solubility	: No data available

## SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: Strong acids. Strong bases. Strong oxidizers.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified  
 Acute toxicity (dermal) : Not classified  
 Acute toxicity (inhalation) : Harmful if inhaled.

Line Marking Paint Various Colours	
ATE AU (dust,mist)	4.672 mg/l/4h
xylene (1330-20-7)	
LD50 oral	4300 mg/kg bodyweight
LD50 dermal	> 5000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 10000 mg/l
Ethyl Acetate (141-78-6)	
LD50 oral	5620 mg/kg bodyweight
LD50 dermal	> 18000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	57700 mg/l
High Mol Wt Wetting Agent	
LC50 Inhalation - Rat [ppm]	0 ppm
LC50 Inhalation - Rat (Dust/Mist)	> 5 mg/l/4h
LC50 Inhalation - Rat (Vapours)	> 20 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
 pH : Not applicable  
 Serious eye damage/irritation : Causes serious eye irritation.  
 pH : Not applicable  
 Respiratory or skin sensitization : May cause an allergic skin reaction.  
 Germ cell mutagenicity : Not classified  
 Carcinogenicity : Not classified  
 Reproductive toxicity : Not classified  
 STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

xylene (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.
Ethyl Acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
High Mol Wt Wetting Agent	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

Aspiration hazard : Not classified.



# PRIMEPAC

*making it easy!*

Line Marking Paint Various Colours	
Vaporizer	Aerosol
Viscosity, kinematic	> 20.5 mm <sup>2</sup> /s Not available
xylene (1330-20-7)	
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
Animal studies and expert judgment for classification	False
Ethyl Acetate (141-78-6)	
Animal studies and expert judgment for classification	False
High Mol Wt Wetting Agent	
Animal studies and expert judgment for classification	False
Viscosity, kinematic	≈ 209000000 mm <sup>2</sup> /s ( 20.00 °C) 99 mm <sup>2</sup> /s ( 40.00 °C)

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

xylene (1330-20-7)	
EC50 - Other aquatic organisms [1]	350 mg/l waterflea
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
Ethyl Acetate (141-78-6)	
EC50 - Other aquatic organisms [1]	717 mg/l waterflea
EC50 - Other aquatic organisms [2]	3300 mg/l
High Mol Wt Wetting Agent	
LOEC (acute)	1 – 10 mg/l
BCF - Other aquatic organisms [2]	≥ 500 mg/l
Partition coefficient n-octanol/water (Log Kow)	≥ 4



0800 277 772



www.primepac.co.nz



sales@primepac.co.nz



L3 1/61 Constellation Drive, Rosedale, Auckland



## 12.2. Persistence and degradability

No additional information available

## 12.3. Bioaccumulative potential

Line Marking Paint Various Colours	
Partition coefficient n-octanol/water (Log Pow)	Not available
High Mol Wt Wetting Agent	
BCF - Other aquatic organisms [2]	≥ 500 mg/l
Partition coefficient n-octanol/water (Log Kow)	≥ 4

## 12.4 Mobility in soil

Line Marking Paint Various Colours	
Partition coefficient n-octanol/water (Log Pow)	Not available
High Mol Wt Wetting Agent	
Partition coefficient n-octanol/water (Log Kow)	≥ 4

## 12.5 Other adverse effects




Ozone : Not classified  
 Other adverse effects : No additional information available

Line Marking Paint Various Colours	
Fluorinated greenhouse gases	False
xylene (1330-20-7)	
Fluorinated greenhouse gases	False
Ethyl Acetate (141-78-6)	
Fluorinated greenhouse gases	False
High Mol Wt Wetting Agent	
Fluorinated greenhouse gases	False

## SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
 Product/Packaging disposal recommendations : When totally empty, containers are recyclable like any other packing.

## SECTION 14: Transport information

ADG	IMDG	IATA
<b>14.1. UN number</b>		
1950	1950	1950
<b>14.2. UN Proper Shipping Name</b>		
AEROSOLS	AEROSOLS	Aerosols, flammable
<b>14.3. Transport hazard class(es)</b>		
2.1	2.1	2.1
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

### 14.6 Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7 Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344, 381  
Limited quantities (ADG) : See SP 277  
Excepted quantities (ADG) : E0  
Packing instructions (ADG) : P207, LP200  
Special packing provisions (ADG) : PP87, L2

#### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

## Air transport

UN-No. (IATA)	: 1950
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

## 14.8 Hazchem or Emergency Action Code

Hazchem Code : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health, and environmental regulations specific for the product in question

#### Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : Listed

#### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Schedule 5

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

### Indication of changes:

Routine Review - No significant changes from the previous issue.

Indication of changes			
Section	Changed item	Change	Comments
	Date of revision	Modified	
	Supersedes	Modified	
2.1	Classification (GHS AU)	Modified	
2.2	Precautionary statements (GHS AU)	Modified	
2.2	Hazard statements (GHS AU)	Modified	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures after skin contact	Modified	
4.2	Symptoms/effects after skin contact	Modified	
7.1	Hygiene measures	Modified	
13.1	Product/Packaging disposal recommendations	Added	
13.1	Waste treatment methods	Modified	

## Data sources

: Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals  
 Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals  
 Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants  
 Safe Work Australia - Hazardous Chemical Information System (HCIS)  
 Australian Inventory of Industrial Chemicals (AICIS Inventory)  
 Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice 2020  
 Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017  
 Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017  
 New Zealand - Chemical Classification and Information Database (CCID)  
 New Zealand - Inventory of Chemicals (NZIoC)  
 European Chemicals Agency (ECHA) - Annex VI (C&L Inventory)  
 European Chemicals Agency (ECHA) - REACH Study Results  
 European Chemicals Agency (ECHA) - REACH Registration Dossiers  
 United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS)  
 Uniform Scheduling of Medicines and Poisons (SUSMP)  
 United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation)  
 Australian Dangerous Goods Code (ADG Code)  
 International Air Transport Association Dangerous Goods Regulations (IATA DGR)  
 International Maritime Dangerous Goods (IMDG Code).

## Date of revision

: 26/08/2024

Classification	
Aerosol 1	H222;H229
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335

Full text of H-statements	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.



0800 277 772



[www.primepac.co.nz](http://www.primepac.co.nz)



[sales@primepac.co.nz](mailto:sales@primepac.co.nz)



L3 1/61 Constellation Drive, Rosedale, Auckland