

PREMIUM GRADE STATIONERY OFFICE TAPE

Made from moisture-stable Polypropylene film and coated one side with a water-based Acrylic Adhesive. Rolls are individually plastic-wrapped and presented in a white labelled box for safe shelf storage or display.

GENERAL PRODUCT INFORMATION

Product	Stationery Tape 18mm x 66m 8 pack
Item Codes	1329
DETAILS	
Adhesive	Acrylic - water-based
Backing	OPP (Oriented Polypropylene)
Colour	Transparent
Total thickness	45 microns (+ 0r -2 microns)
Adhesion to steel	5.0 N/25mm
Elongation	100% at break
Latex Free	Yes
Shelf Life	12 months from the manufacturing date (correct storage)
Roll Sizes	12, 18 mm x 33 m 12, 18 & 24 mm x 66 m

Can be slit up to 66m in length rolls.

FEATURES

Good age-resistant properties	Very good ageing properties (non-yellowing).
Moisture resistance	Has good moisture-resistant properties
Hand tearable	Easily torn by hand for fast and effective use.
Invisible & writable	The invisible tape can be written and typed on and photocopied without being seen.

TYPICAL APPLICATIONS

- Excellent for multi-purpose use in the office, school, library and home.
- Used for various invisible mending/repairs, splicing, and joining applications.
- Sealing plastic bags, gift wrapping & lid airtight closure.
- Quick and easy to use - excellent for mending drawings, library books, blueprints and legal documents.
- The tape can be written and typed on and is invisible when photocopied.



PRIMEPAC

making it easy!

ADVANTAGES

Quick & Easy to Use	No cleanup mess, which occurs with liquid adhesives.
Slit to Size in NZ	Roll widths are slit to the required sizes in New Zealand. Fast delivery to the site throughout New Zealand.
Free Technical Advice	Free technical assistance, samples and advice available throughout NZ from the tape spec sales team.

SURFACE SUBSTRATE CONDITION & PREPARATION

The surfaces to be bonded must be dry & free from any contamination, including dust, oils, fats, oxidation, release agents & any other known contamination.

The correct choice of surface cleaner depends on the surface properties. Essentially, non-greasy cleaners are recommended, including isopropanol alcohol (mixed 50/50 with clean water). Cleaning cloths must be clean, grease & fat-free with no loose fibres or cloth particles.

The bond strength is dependent upon the contact pressure of the adhesive to the substrate. To assist this process, all adhesive tapes require firm hand or roller pressure.

BONDING APPLICATION TEMPERATURE

We recommend that the product, substrate and environment should be between +15°C & 25°C. Ensure that the adhesive product & substrates are allowed to adjust to the environmental temperature before bonding. For product storage, we recommend that products be stored in their original packaging under dry conditions, ideally at room temperature but not warmer than +25°C. High relative humidity & direct sunlight must be avoided at all costs.

For more detailed handling instructions, please refer to our comprehensive application guide.

PRODUCT USE

The information in this guide is based upon our knowledge & practical experience. This data is intended only as a source of information given without guarantee & does not constitute a warranty.

Due to the wide variety of possible uses & applications, customers should independently determine the suitability of these products for their specific purpose before use. Trial samples are provided free of charge & without obligation.

For detailed surface preparation & application information, please refer to our detailed Surface Condition & Preparation Guide.

NOTE: We recommend tape product testing to assess the suitability of the selected product to the end application & conditions.



0800 277 772



www.primepac.co.nz



sales@primepac.co.nz



L3 1/61 Constellation Drive, Rosedale, Auckland